







EE Beta Radiator Guards Installation Instructions



WARNING AND DISCLAIMER

All parts manufactured, designed or sold by Enduro Engineering, Inc. (EEI) are to be installed by a licensed motorcycle dealer or a licensed motorcycle technician. Motorcycles can be dangerous. Serious injury, death and property damage can result from the use of motorcycles. This risk is increased by improper installation or misuse of after market parts. EEI's customers must exercise good judgment in the use, control, alteration, part selection and installation, and maintenance of their motorcycles. In the event of a possible defect in material or design, or any other defect in a part manufactured, designed or sold by EEI, the responsibility of EEI is limited to either a refund of the purchase price or the replacement of the part if EEI determines the part to be defective, and subject to EEI's inspection of the part within thirty (30) days from the date of purchase. (Note: any attempted repairs or modifications made to EEI products will void this limited warranty). EEI, under no circumstances will be responsible for incidental and/or consequential damages, property damage, personal injury damage, or damage, injury, cost or expense of any kind or nature whatsoever. By purchasing an EEI product or a product sold by EEI, you (1) acknowledge the above disclaimer and agree to its terms; (2) agree that any claim brought against EEI arising from and/or pertaining to or otherwise related to a part manufactured, designed or sold by EEI must be brought in the Michigan State Courts located in the County of Ingham or in the Federal District Court for the Western District of Michigan and that Michigan law shall apply on all issues; and (3) any claim against EEI must be brought within one (1) year of purchase of the product. EEI makes no other warranty, express or implied, including without limitation any warranties of merchantability and fitness for a particular purpose. R.JRF.Sec.randt.warninganddisclaimer. 5 2 08

Note: Installation of this product requires the use of Enduro Engineering 11-400 radiator braces.

- 1** Remove the seat by compressing the button to the left of the seat. (Fig 1)
- 2** Using a 4mm allen wrench remove the front and rear gas tank bolts. (Fig 2 and Fig 3)
- 3** Using an 8mm t-handle or socket remove the left & right shroud bolts. (Fig 4)
- 4** Disconnect the fuel line from the carburetor or throttle body.
- 5** Remove the gas tank and shrouds.
- 6** Push the plastic radiator louvers toward the outside of the bike and remove them from the front of the radiators. (Fig 5)
- 7** Using an 8mm t-handle or socket remove the 4 bolts holding the radiators to the frame. (Fig 6)
- 8** Using the provided 6x16mm button head bolts; attach the smaller "inside" piece of the EE radiator brace to one side of the radiator guard. (Fig 7)
Note: Be sure to use the appropriate side radiator guard, they are labeled (400R and 400L).
- 9** While gently rotating the radiator out of the way, slide the radiator guard assembly into location. (Fig 8)
Note: If your model has a horn, you can attach the horn bracket to the right side radiator brace using the provided 6x8mm button head bolt. (Fig 8.1)
- 10** Attach the radiator and radiator guard assembly using the hardware provided with the 11-400 radiator brace. (Fig 9)
- 11** Repeat steps 3-5 on the opposite side of the bike.
- 12** Install the right radiator with brace and guard back on the bike.
- 13** Repeat steps 3 thru 7 for the left side guard.
- 14** Reinstall the gas tank and the gas tank mounting bolt.
- 15** Reinstall the stock two shroud bolts.
- 16** Reinstall the seat.



QUALITY OFF-ROAD MOTORCYCLE PRODUCTS

INSTRUCTIONS

EE Beta Radiator Guards

Part# 12-400