## **KTM Off-Road Lighting Kit Instructions**

Enduro Engineering Off-Road Lighting Kits are not intended for highway use and are not DOT approved.

- Remove seat and gas tank
- 2 Attach the ground wire of the wiring harness and the ground wire of the voltage regulator to the frame and unravel the harness. Route the headlight wiring up the right side of the frame. (Fig 1)

Attach the voltage regulator to the frame by first drilling a larger hole in the frame tab in front of the tapped hole and then using the supplied 6x36 Allen head bolt and lock nut. Attach the yellow wire from the voltage regulator to the white wire of the new harness. Attach the yellow wire from the new harness to the yellow wire on the harness coming from the engine. (Fig 1)

- Remove the two 5x16mm rear fender bolts and shoulder washers from the sub frame under the rear fender.
- Remove 17 mm sub frame rear fender nut and hollow bolt. See (Fig 2)
- Slightly pull down black rear fender flap and insert tail light wiring harness along the sub frame rail in to the air box as shown. (Fig 3)
- 6 Pull the harness through, taking up the slack in the wiring harness.
- Re-install 17mm sub frame bolt and hollow nut. (Fig 2)
- Place the taillight assembly up to the bottom of the rear fender.

  Apply a small amount of thread lock to the two supplied 5x20mm hex bolts and attach the tail light assembly to the sub frame. These bolts will take the place of the 5x16mm bolts and
- shoulder washers that you removed in step 3. (Fig 4)
- Drill a  $\frac{1}{4}$  hole through the black plastic tail light holder and through the rear fender. (Fig 5) Insert and tighten supplied 6x20 button head bolt using flat washers and lock nut.
- 10 Plug the tail light harness into the connector in the air box just above the filter. (Fig 6)
- 11 Re-install seat and gas tank
- 12 Remove the number plate.
- 13 Remove brake hose quide from headlight mask.
- Place brake hose behind guide and re-install brake hose guide on headlight mask. NOTE: Brake hose is properly routed when it is between guide and headlight mask. (Fig 7)
- Plug headlight into the wiring harness and plug the yellow and white wires from the wiring harness into headlight switch on the headlight. (Fig 8)
- Set the headlight on to the plastic posts that the number plate came off from and fasten the rubber headlight straps around fork legs.

















## WARNING AND DISCLAIMER

All parts manufactured, designed or sold by Enduro Engineering, Inc. (EEI) are to be installed by a licensed motorcycle dealer or a licensed motorcycle technician. Motorcycles can be dangerous. Serious injury, death and property damage can result from the use of motorcycles. This risk is increased by improper installation or misuse of after market parts. EEI's customers must exercise good judgment in the use, control, alteration, part selection and installation, and maintenance of their motorcycles. In the event of a possible defect in material or design, or any other defect in a part manufactured, designed or sold by EEI, the responsibility of EEI is limited to either a refund of the purchase price or the replacement of the part if EEI determines the part to be defective, and subject to EEI's inspection of the part within thirty (30) days from the date of purchase. (Note: any attempted repairs or modifications made to EEI products will void this limited warranty). EEI, under no circumstances will be responsible for incidental and/or consequential damages, property damage, personal injury damage, or damage, injury, cost or expense of any kind or nature whatsoever. By purchasing an EEI product or a product sold by EEI, you (1) acknowledge the above disclaimer and agree to its terms; (2) agree that any claim brought against EEI arising from and/or pertaining to or otherwise related to a part manufactured, designed or sold by EEI must be brought in the Michigan State Courts located in the County of Ingham or in the Federal District Court for the Western District of Michigan and that Michigan law shall apply on all issues; and (3) any claim against EEI must be brought within one (1) year of purchase of the product. EEI makes no other warranty, express or implied, including without limitation any warranties of merchantability and fitness for a particular purpose, R.JRF.Sec.randt.warninganddisclaimer.5 2 08



QUALITY OFF-ROAD MOTORCYCLE PRODUCTS

## INSTRUCTIONS

KTM Off-Road Lighting Kit

Part# 30-701