

Decide where you want to install your chainsaw mount. You can mount on the roll cage bar, or if you have the 1 inch bar on the bed rails, you can mount there also. Flip over to the backside for bedrail installation instructions.

Roll Cage Location Installation Instructions.

1. Install the included composite blocks into the 2 center holes on the chainsaw mounts using the provided M6x20 button head bolts. Tighten using a 4mm Allen wrench. (FIG 1)
2. Slide the included rubber straps through each composite block in the pre cut slots. (FIG 2)
3. Line up the chainsaw mount blocks to your roll cage where you would like for the chainsaw mount to be positioned. (FIG 3)
4. Wrap each of the two rubber straps around the roll cage bar and tighten down. (FIG 4) (The straps are very durable, you can put a good amount of pressure on them when tightening)
5. With the chainsaw strap hanging loose off the front, slide your chainsaw into the scabbard. (FIG 5)
6. Pull the chainsaw strap up over the chainsaw near the handle. Tighten strap down to secure the chainsaw in place. (FIG 6)
7. Have fun and enjoy your next project!



FIG 1



FIG 2



FIG 3



FIG 4



FIG 5



FIG 6

WARNING AND DISCLAIMER

All parts manufactured, designed or sold by Enduro Engineering, Inc. (EEI) are to be installed by a licensed motorcycle dealer or a licensed motorcycle technician. Motorcycles can be dangerous. Serious injury, death and property damage can result from the use of motorcycles. This risk is increased by improper installation or misuse of after market parts. EEI's customers must exercise good judgement in the use, control, alteration, part selection and installation, and maintenance of their motorcycles. In the event of a possible defect in material or design, or any other defect in a part manufactured, designed or sold by EEI, the responsibility of EEI is limited to either a refund of the purchase price or the replacement of the part if EEI determines the part to be defective, and subject to EEI's inspection of the part within thirty (30) days from the date of purchase. (Note: any attempted repairs or modifications made to EEI Products will void this limited warranty.) EEI, under no circumstances will be responsible for incidental and/or consequential damages, property damage, personal injury damage, or damage, injury, cost or expense of any kind or nature whatsoever. By purchasing as EEI product or a product sold by EEI, you (1) acknowledge the above disclaimer and agree to its terms; (2) agree that any claim brought against EEI arising from and/or pertaining to or otherwise related to a part manufactured, designed or sold by EEI must be brought in the Michigan State Courts located in the County of Ingham or in the Federal District Court for the Western District of Michigan and the Michigan law shall apply on all issues; and (3) any claim against EEI must be brought within one (1) year of purchase of the product. EEI makes no other warranty, express or implied, including without limitation any warranties of merchantability and fitness for a particular purpose.

PART NUMBER: 25-CSM-DEERE
John Deere Gator Chainsaw Mount

Installation Instructions
Quality Off-Road Motorcycle Products



Bed Rail Location Installation Instructions

1. Install the two provided aluminum clamps on to the location of the bed rail that you want the chainsaw mount to be mounted. Using the provided M6x25 socket head bolts. Get the mount snug to the rail but loose enough you can move them. (FIG 1)
2. Line up the chainsaw mount to the clamps in the desired location and mounting holes you wish to use. There are three slotted mounting holes on the chainsaw mount you can use. (FIG 2)
3. After lining up the clamps for your desired mounting holes. Use a 5mm Allen wrench to tighten the clamp socket head bolts. (FIG 3)
4. Line the Chainsaw back up to the clamps. Using the provided M6x16 button head bolts, mount the chainsaw mount to the clamps. Tighten button head bolts using a 4mm Allen wrench. (FIG 4)
5. With the chainsaw strap hanging loose off the front, slide your chainsaw into the scabbard. (FIG 5)
6. Pull the chainsaw strap up over the chainsaw near the handle. Tighten strap down to secure the chainsaw in place. (FIG 6)
7. Have fun and enjoy your next project!



FIG 1



FIG 2



FIG 3



FIG 4



FIG 5



FIG 6