

Yamaha Skid Plate Instructions

1 Remove the factory skid plate; there are three bolts (two in the front and one below).

2 Position the rear clamp (573-02) above the frame tab that the factory skid plate mounted to, **See photo 1.0**. Insert the provided 6x20 Button head bolt into the tab.

NOTICE: This bolt is intended to hold the clamp in location during the install, not to fasten the clamp to the frame tab. **See photo 1.1**.

3 Locate the EE skid plate so that the front two mounting holes align with the factory mounting holes on the frame. **See photo 2.0**. Insert the two provided 6x16 hex head bolts along with the provided washers, only finger tighten at this time.

4 Arrange the provided 8 x 40 flat head bolts through the skidplate and supplied spacer as shown in **photo 3.0**. Rotate the skid plate up toward the frame aligning the 8x40 bolts with the clamp that was installed in step #2.

5 Once all mounting bolts have been started, you can now tighten them, alternating from front to back until skid plate is secure.



PHOTO 1.0



PHOTO 2.0



PHOTO 1.1



PHOTO 3.0

WARNING AND DISCLAIMER

All parts manufactured, designed or sold by Enduro Engineering, Inc. (EEI) are to be installed by a licensed motorcycle dealer or a licensed motorcycle technician. Motorcycles can be dangerous. Serious injury, death and property damage can result from the use of motorcycles. This risk is increased by improper installation or misuse of after market parts. EEI's customers must exercise good judgment in the use, control, alteration, part selection and installation, and maintenance of their motorcycles. In the event of a possible defect in material or design, or any other defect in a part manufactured, designed or sold by EEI, the responsibility of EEI is limited to either a refund of the purchase price or the replacement of the part if EEI determines the part to be defective, and subject to EEI's inspection of the part within thirty (30) days from the date of purchase. (Note: any attempted repairs or modifications made to EEI products will void this limited warranty). EEI, under no circumstances will be responsible for incidental and/or consequential damages, property damage, personal injury damage, or damage, injury, cost or expense of any kind or nature whatsoever. By purchasing an EEI product or a product sold by EEI, you (1) acknowledge the above disclaimer and agree to its terms; (2) agree that any claim brought against EEI arising from and/or pertaining to or otherwise related to a part manufactured, designed or sold by EEI must be brought in the Michigan State Courts located in the County of Ingham or in the Federal District Court for the Western District of Michigan and that Michigan law shall apply on all issues; and (3) any claim against EEI must be brought within one (1) year of purchase of the product. EEI makes no other warranty, express or implied, including without limitation any warranties of merchantability and fitness for a particular purpose. RJRF.Sec.randt.warninganddisclaimer.5 2 08



QUALITY OFF-ROAD MOTORCYCLE PRODUCTS

INSTRUCTIONS

Yamaha Skid Plate Instructions
Part# 24-574, 24-576