




1. Remove the seat by pressing the button on the left towards the rear of the Motorcycle. (fig. 1)
2. Turn off the fuel valve, and disconnect the fuel line.
3. Using an 8mm socket remove the two bolts securing the tank and each of the lower shroud bolts. (fig. 2 , fig. 2.1 and 2.2)
4. Remove the plastic radiator louvers (fig. 3)
5. Using an 8mm socket remove the two radiator mounting bolts (fig. 4)
6. Using the supplied M6x16mm button head bolts fasten the radiator rods to the part labeled 4018 R/L1 tighten at this time. (right or left side) (fig. 5)
7. While holding the radiator away from the frame install the assembly from the previous step between the radiator and the frame (fig. 6)
8. Using the provided M6x16 hex head bolt, 22mm washer and spacer as shown in fig. 7 fasten the radiator and brace to the frame leave bolts loose at this time. (fig. 7 and Fig. 7.1)
9. Connect the outer radiator brace labeled 4018 R/L2 (right or left side) Use the provided M6x8mm button head bolts to connect the back side of the radiator brace. Use the provided M6x16mm button head bolts to secure both of the radiator rods. (Fig. 8 and 8.1)
10. Now go back through tighten all bolts.
11. Put the radiator louvers back on the bike (fig. 3).
12. Put the tank back on the bike. Use the OEM hardware for the two tank mount locations. Reconnect the fuel line.
13. Using the supplied rubber straps, secure the lower portion of the radiator shrouds as shown. (Fig. 9)
14. Put the seat back on.



## WARNING AND DISCLAIMER

All parts manufactured, designed or sold by Enduro Engineering, Inc. (EEI) are to be installed by a licensed motorcycle dealer or a licensed motorcycle technician. Motorcycles can be dangerous. Serious injury, death and property damage can result from the use of motorcycles. This risk is increased by improper installation or misuse of after market parts. EEI's customers must exercise good judgment in the use, control, alteration, part selection and installation, and maintenance of their motorcycles. In the event of a possible defect in material or design, or any other defect in a part manufactured, designed or sold by EEI, the responsibility of EEI is limited to either a refund of the purchase price or the replacement of the part if EEI determines the part to be defective, and subject to EEI's inspection of the part within thirty (30) days from the date of purchase. (Note: any attempted repairs or modifications made to EEI products will void this limited warranty). EEI, under no circumstances will be responsible for incidental and/or consequential damages, property damage, personal injury damage, or damage, injury, cost or expense of any kind or nature whatsoever. By purchasing an EEI product or a product sold by EEI, you (1) acknowledge the above disclaimer and agree to its terms; (2) agree that any claim brought against EEI arising from and/or pertaining to or otherwise related to a part manufactured, designed or sold by EEI must be brought in the Michigan State Courts located in the County of Ingham or in the Federal District Court for the Western District of Michigan and that Michigan law shall apply on all issues; and (3) any claim against EEI must be brought within one (1) year of purchase of the product. EEI makes no other warranty, express or implied, including without limitation any warranties of merchantability and fitness for a particular purpose.

Part # 11-4018

## Radiator Brace Instructions

Quality Off-Road Motorcycle Products

