EE Seat Cover Installation Instructions

NOTE: We recommend using a pneumatic staple gun with ¼ staples to install this seat cover. Most hand held manual staple guns will not be powerful enough to drive the staples all the way into the seat base. You will also need a staple puller or a straight blade screwdriver and needle nose pliers.



- Remove seat from bike.
- 2 On 2003 and earlier model KTM's it will be necessary to remove the 2 seat mount brackets from the back of the seat base. Use a 10mm socket or t-handle to remove the 4 seat bracket mount bolts.
- Using a staple puller or a flat blade screw driver, pry the old staples up (Figure 1) and remove them from the seat base. If a staple doesn't come all the way out, pull it out with a pair of needle nose pliers. Do not leave any old staples in the seat base.
- Remove the old seat cover.
- Make sure that the seat foam is in good condition. If not, replace it.

 Also, make sure that the seat base is in good shape and not
 damaged or cracked. If the seat base needs replacement, an EE
 complete seat would be your best option.
- 6 Slip the new seat cover over the front of the seat base. Pull the front of the seat cover down snug over the front of the seat base. Using a staple gun, put 3 staples in the front part of the seat cover to hold it in place. (Figure 2) Now pull the rear of the seat cover over the back of the seat base. Pay close attention to keeping the EE logo on the back of the seat cover centered. (Figure 3) Put 3 staples in the rear of the seat cover to hold it in place. (Figure 4)
- Pull both sides of the middle part of the seat cover down over seat base and put 3 staples in each side to hold it in place. (Figure 5)

 Now work your way from back to front pulling the seat cover over the seat base and stapling it in place as you go. Take your time and make sure you leave no wrinkles in the seat cover. If you do leave a wrinkle, determine which way you need to move the seat cover to remove the wrinkle. Then pull a few staples at a time, work the area of the seat cover to remove the wrinkle, and then re-staple that area of the cover.
- On 2003 and earlier models, re-install the seat mount brackets.
- Re-install seat on bike.











WARNING AND DISCLAIMER

All parts manufactured, designed or sold by Enduro Engineering, Inc. (EEI) are to be installed by a licensed motorcycle dealer or a licensed motorcycle technician. Motorcycles can be dangerous. Serious injury, death and property damage can result from the use of motorcycles. This risk is increased by improper installation or misuse of after market parts, EEI's customers must exercise good judgment in the use, control, alteration, part selection and installation, and maintenance of their motorcycles. In the event of a possible defect in material or design, or any other defect in a part manufactured, designed or sold by EEI, the responsibility of EEI is limited to either a refund of the purchase price or the replacement of the part if EEI determines the part to be defective, and subject to EEI's inspection of the part within thirty (30) days from the date of purchase. (Note: any attempted repairs or modifications made to EEI products will void this limited warranty). EEI, under no circumstances will be responsible for incidental and/or consequential damages, property damage, personal injury damage, or damage, injury, cost or expense of any kind or nature whatsoever. By purchasing an EEI product or a product sold by EEI, you (1) acknowledge the above disclaimer and agree to its terms; (2) agree that any claim brought against EEI arising from and/or pertaining to or otherwise related to a part manufactured, designed or sold by EEI must be brought in the Michigan State Courts located in the County of Ingham or in the Federal District Court for the Western District of Michigan and that Michigan law shall apply on all issues: and (3) any claim against FEI must be brought within one (1) year of purchase of the product. EEI makes no other warranty, express or implied, including without limitation any warranties of merchantability and fitness for a particular purpose R.JRF.Sec.randt.warninganddisclaimer. 5 2 08



QUALITY OFF-ROAD MOTORCYCLE PRODUCTS

INSTRUCTIONS

EE Seat Cover