





Radiator Brace Installation



- 1 Remove the seat and both radiator shrouds. Remove the radiator louvers from the front side of the radiators.
- 2 Drain the coolant by using an 8mm socket or t-handle to remove the drain bolt on the water pump cover. (Figure 1) Remove the radiator cap to speed up the draining process.
- 3 Once the coolant has drained, re-install the drain plug on the water pump cover.
- 4 Using a Phillips head screw driver or a 6mm socket, loosen the three hose clamps on the right radiator and the two hose clamps on the left radiator. Slide all of the hoses off of the radiators.
- 5 Using an 8mm socket or t-handle, remove the four radiator mounting bolts (two on each side) and remove the radiators.
- 6 Use 2 of the supplied 6x16mm button head bolts to install 2 of the supplied support rods on the big brace half marked with an "R". (Figure 2) Use 1 of the supplied 6x16mm button head bolts to install 1 of the supplied support rods on the top of the big brace half marked with an "L". NOTE: The left side bottom support rod cannot be installed until after step 10 is complete.
- 7 Slip the big brace half marked "R" over the right radiator so that the "R" marking is facing the top back part of the radiator. The support rods should be in front of the radiator. (Figure 3). Slip the big brace half marked "L" over the left radiator in the same manner.
- 8 In place of the stock radiator mounting bolts, use the 4 supplied 6x35mm hex head bolts with the 4 supplied flat washers and the 4 supplied aluminum spacers between the big brace halves and the radiator (Figure 4) to re-install the radiators with the big brace halves on the bike. (Figure 5) Tighten all 4 bolts.
- 9 Re-connect all of the radiator hoses and tighten all hose clamps.
- 10 Re-install the radiator louvers at this time. Be sure that the left louver is seated properly over the bottom of the left radiator.
- 11 Using 1 of the supplied 6x16mm bolts, install the bottom support rod on the left big brace half. (Figure 6)
- 12 Using 2 of the supplied 6x8mm button head bolts mount the small brace half marked "L" on the tabs of the left side big brace half. (Figure 7) Using 2 of the supplied 6x16mm bolts, attach the small brace half to the upper and lower support rods. (Figure 8)
- 13 Repeat step 12 for the right side.
- 14 Mount the left radiator shroud to the gas tank by threading the 2 stock mounting bolts into the mounting holes in the gas tank. Do not tighten yet. Next attach the radiator shroud to the radiator by using the longer supplied 6x25mm hex head bolt (in place of the stock mounting bolt) with the stock shoulder washer along with the supplied .350" aluminum spacer between the radiator shroud and the radiator. (Figure 9) Now attach the shroud to the bike frame by using the longer supplied 6x20mm hex head bolt (in place of the stock mounting bolt) with the stock shoulder washer along with the supplied .350" aluminum spacer between the radiator shroud and the bike frame. (Figure 10) Tighten all the left radiator shroud mounting bolts.
- 15 Repeat step 14 for the right radiator shroud.
- 16 Re-install the seat.
- 17 Fill the cooling system with coolant. Bleed the cooling system if necessary. NOTE: Consult motorcycle manufacturer's service manual for specific cooling system bleeding procedures.



WARNING AND DISCLAIMER

All parts manufactured, designed or sold by Enduro Engineering, Inc. (EEI) are to be installed by a licensed motorcycle dealer or a licensed motorcycle technician. Motorcycles can be dangerous. Serious injury, death and property damage can result from the use of motorcycles. This risk is increased by improper installation or misuse of after market parts. EEI's customers must exercise good judgment in the use, control, alteration, part selection and installation, and maintenance of their motorcycles. In the event of a possible defect in material or design, or any other defect in a part manufactured, designed or sold by EEI, the responsibility of EEI is limited to either a refund of the purchase price or the replacement of the part if EEI determines the part to be defective, and subject to EEI's inspection of the part within thirty (30) days from the date of purchase. (Note: any attempted repairs or modifications made to EEI products will void this limited warranty). EEI, under no circumstances will be responsible for incidental and/or consequential damages, property damage, personal injury damage, or damage, injury, cost or expense of any kind or nature whatsoever. By purchasing an EEI product or a product sold by EEI, you (1) acknowledge the above disclaimer and agree to its terms; (2) agree that any claim brought against EEI arising from and/or pertaining to or otherwise related to a part manufactured, designed or sold by EEI must be brought in the Michigan State Courts located in the County of Ingham or in the Federal District Court for the Western District of Michigan and that Michigan law shall apply on all issues; and (3) any claim against EEI must be brought within one (1) year of purchase of the product. EEI makes no other warranty, express or implied, including without limitation any warranties of merchantability and fitness for a particular purpose. R.JRF.Sec. randt.warninganddisclaimer.5 2 08

Enduro Engineering

QUALITY OFF-ROAD MOTORCYCLE PRODUCTS

INSTRUCTIONS

Radiator Brace Installation

Part# 11-170, 11-171, 11-173, 11-174